APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/691,004	10/18/2000	Leonard Forbes	303.324US4	4509

7590   09/02/2003

Schwegman, Lundberg, Woessner & Kluth, P.A.
P.O.Box 2938
Minneapolis, MN 55402

EXAMINER
MONDT, JOHANNES P

ART UNIT	PAPER NUMBER
2826	

DATE MAILED: 09/02/2003

Please find below and/or attached an Office communication concerning this application or proceeding.

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) FROM
THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR.1.136(a). In no event, however, may a reply be timely filed
  after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any
  earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on *31 July 2003* .

2a)☐ This action is **FINAL.**   2b)☒ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) *36-39,59-67,71-85,98 and 99* is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☒ Claim(s) *83-85* is/are allowed.

6)☒ Claim(s) *36-39,59-67,71-82,98 and 99* is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☐ The drawing(s) filed on _____ is/are: a)☐ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

11)☐ The proposed drawing correction filed on _____ is: a)☐ approved b)☐ disapproved by the Examiner.

    If approved, corrected drawings are required in reply to this Office action.

12)☐ The oath or declaration is objected to by the Examiner.

Priority under 35 U.S.C. §§ 119 and 120

13)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All b)☐ Some * c)☐ None of:

        1.☐ Certified copies of the priority documents have been received.

        2.☐ Certified copies of the priority documents have been received in Application No. _____ .

        3.☐ Copies of the certified copies of the priority documents have been received in this National Stage
application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

14)☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application).

    a) ☐ The translation of the foreign language provisional application has been received.

15)☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☒ Information Disclosure Statement(s) (PTO-1449) Paper No(s) <u>17</u> .

4) ☐ Interview Summary (PTO-413) Paper No(s). _____ .

5) ☐ Notice of Informal Patent Application (PTO-152)

6) ☐ Other: .

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1.   A request for continued examination under 37 CFR 1.114, including the fee set

forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this

application is eligible for continued examination under 37 CFR 1.114, and the fee set

forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action

has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 7/31/3

has been entered.

Response to Arguments

2.   Applicant's arguments filed 7/31/3 have been fully considered. The following

rejections and indication of allowable subject matter are the result.

Claim Rejections - 35 USC § 102

3.   The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that

form the basis for the rejections under this section made in this Office action:

> A person shall be entitled to a patent unless –
>
> (e) the invention was described in a patent granted on an application for patent by another filed in the United States before the invention thereof by the applicant for patent, or on an international application by another who has fulfilled the requirements of paragraphs (1), (2), and (4) of section 371(c) of this title before the invention thereof by the applicant for patent.

The changes made to 35 U.S.C. 102(e) by the American Inventors Protection Act of

1999 (AIPA) and the Intellectual Property and High Technology Technical Amendments Act of

2002 do not apply when the reference is a U.S. patent resulting directly or indirectly from an

international application filed before November 29, 2000. Therefore, the prior art date of the

reference is determined under 35 U.S.C. 102(e) prior to the amendment by the AIPA (pre-AIPA

35 U.S.C. 102(e)).

4.   *Claim 37* is rejected under 35 U.S.C. 102(e) as being anticipated by Weitzel et al

(5,661,312). Weitzel et al teach a source region 21 (cf. col. 2, l. 2), a drain region 11 (cf.

col. 1, l. 42-44 and col. 2, l. 4-5), a channel region 14 (cf. col. 1, 50) between said

source region and said drain region, and a gate 18 (cf. col. 1, l. 57-58) separated from

said channel region by an insulator 17 (cf. col. 1, 52), and furthermore are inherent in

the device by Weitzel et al, because all of the above limitations are inherent in a

MOSFET as disclosed by Weitzel et al in their abstract and claimed (claim1 for

instance). Furthermore, the gate as claimed in by Weitzel et al in their claim 2

dependent upon their claim 1, is in one embodiment made of a silicon carbide

compound $Si_{1-x}C_x$ with x=0.5, namely: silicon carbide (SiC). Therefore, Weitzel et al

teach the gate formed of a silicon carbide compound $Si_{1-x}C_x$ with x selected at a

predetermined value approximately between 0.5 and 1.0. The value for x of the prior art

is thus seen to be within the claimed range defined in claim 37. The purpose as

claimed, i.e., "to establish a desired value of a barrier energy between the gate and the

insulator" is irrelevant for the present device claim, for which only the final structure

matters.

Claim Rejections - 35 USC § 103

5.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

6.   ***Claim 36 and 38-39*** are rejected under 35 U.S.C. 103(a) as being unpatentable

over Chiang et al (4,598,305) in view of Halvis et al (5,369,040). Chiang et al teach (cf.

Fig. 1) a transistor comprising a source region, a drain region, a channel region

between the source and drain regions (regions 26, 28 are the source/drain regions, and

16 is a channel region) (cf. col. 3, l. 32-66); and a (polysilicon) gate 22 separated from

the channel region by an insulator 20 (cf. col. 3, l. 32-66). The gate 22 according to

Chiang is of silicon (cf. col. 3, l. 32-66). Although Chiang et al do not necessarily teach

the gate material to be $Si_{1-x}C_x$ with x between 0.5 and 1.0, it would have been obvious

to replace the poly-silicon gate material with $Si_{1-x}C_x$ with x being infinitesimally close to

the range x greater than 0.5 in view of Halvis et al, who teach in the art of MOS photo-

detectors (cf. title and abstract), hence analogous art, that the gate can be made more

transparent by adding up to 50% carbon to the poly-silicon, thus creating a

polycrystalline silicon carbide compound gate, thereby increasing the efficiency of the

device (cf. abstract and col. 3, l. 32-43). Applicant's disclosure does not explain why it

is critical to the invention to make x infinitesimally greater than 0.5 instead of

infinitesimally less than 0.5: the "Summary of the Invention" rather allows for the range 0

< x < 1 (see pages 3-5), while other claims in the same invention cover rather

complementary ranges, such as $0.1 < x < 0.5$. Furthermore, according to Applicant the

value of x in one embodiment is selected to establish a desired value for the barrier

energy between the gate and the underlying insulator; however, the energy gap of $Si_{1-x}C_x$, and hence said barrier energy is a continuous function of the stoichiometric

parameter x. Therefore, said barrier energy has substantially the same value for $x=0.5$

and for x infinitesimally greater than 0.5. The burden is to Applicant to show otherwise,

i.e., to show said infinitesimal difference in x makes a critical difference in the invention.

Applicant is reminded that a *prima facie* case of obviousness typically exists when the

ranges of a claimed composition overlap the ranges disclosed in the prior art or when

the ranges of a claimed composition do not overlap but are close enough such that one

skilled in the art would have expected them to have the same properties. In re Peterson,

65 USPQ2d 1379 (CA FC 2003).

On claim 38: The barrier energy between the gate material in the device as

essentially taught by Chiang et al and Halvis et al is the barrier energy between silicon

dioxide (cf. col. 3, l. 56-58 in Chiang et al) and $Si_{1-x}C_x$ with x infinitesimally close to but

less than 0.5; said barrier energy is therefore infinitesimally close to a boundary in the

claimed range, namely 2.8 eV. Applicant neither discloses nor explains in the

Specification why said infinitesimal difference is critical to the invention. Applicant is

reminded that a *prima facie* case of obviousness typically exists when the ranges of a

claimed composition overlap the ranges disclosed in the prior art or when the ranges of

a claimed composition do not overlap but are close enough such that one skilled in the

art would have expected them to have the same properties. In re Peterson, 65 USPQ2d

1379 (CA FC 2003).

On claim 39: the insulator in the invention as essentially taught by Chiang et al

and Halvis et al is formed of silicon dioxide (cf. col. 3, l. 56-58 in Chiang et al).

7.   **Claims 59-61** are rejected under 35 U.S.C. 103(a) as being unpatentable over

Chiang et al (4,598,305) and Halvis et al (5,369,040). Chiang et al teach (cf. Fig. 1) a

transistor comprising a source region and a drain region (regions 26 and 28) formed in a

substrate 12/14/22, a channel region 16 in the substrate between the source and drain

regions (cf. col. 3, l. 32-66); and a (polysilicon) gate 22 separated from the channel

region by an insulator 20 (cf. col. 3, l. 32-66). The gate 22 according to Chiang is of

silicon (cf. col. 3, l. 32-66). Although Chiang et al do not necessarily teach the gate

material to be $Si_{1-x}C_x$ with x between approximately 0.5 and 1.0, it would have been

obvious to replace the poly-silicon gate material with $Si_{1-x}C_x$ with x up to 0.5 in view of

Halvis et al, who teach in the art of MOS photo-detectors (cf. title and abstract), hence

analogous art, that the gate can be made more transparent by adding up to 50% carbon

to the poly-silicon, thus creating a polycrystalline silicon carbide compound gate,

thereby increasing the efficiency of the device (cf. abstract and col. 3, l. 32-43).

Applicant's disclosure does not explain why it is critical to the invention to make x

infinitesimally greater than 0.5 thus fulfilling the limitation in the claim, instead of

infinitesimally less than 0.5 as taught by Halvis et al: the "Summary of the Invention"

rather allows for the range $0 < x < 1$ (see pages 3-5), while other claims in the same

invention cover rather complementary ranges, such as $0.1 < x < 0.5$. Furthermore,

according to Applicant the value of x in one embodiment is selected to establish a

desired value for the barrier energy between the gate and the underlying insulator;

however, the energy gap of $Si_{1-x}C_x$, and hence said barrier energy is a continuous

function of the stoichiometric parameter x (a polynomial). Therefore, said barrier energy

has substantially the same value for $x=0.5$ and for x infinitesimally greater than 0.5. The

burden is to Applicant to show otherwise, i.e., to show said infinitesimal difference in x

makes a critical difference in the invention. Applicant is reminded that a *prima facie*

case of obviousness typically exists when the ranges of a claimed composition overlap

the ranges disclosed in the prior art or when the ranges of a claimed composition do not

overlap but are close enough such that one skilled in the art would have expected them

to have the same properties. In re Peterson, 65 USPQ2d 1379 (CA FC 2003). Because

the device by Chiang et al detects light that traverses the gate material there is ample

motivation to include the teaching by Halvis et al in this respect in the device by Chiang

et al. Combination of said teaching and said device is straightforward by adding

methane gas during poly-silicon growth or using ion implantation as recommended by

Halvis et al (cf. col. 3, l. 44-51). Success in implementing the combination can therefore

be reasonably expected.

On claim 60: the substrate in the device by Chiang et al comprises a p-type

silicon substrate 14 (cf. col. 3, l. 46-55); the source region comprises an n+ type source

region formed in the substrate and the drain region comprises an n+ type drain region in

the substrate (regions 26 and 28, respectively) (cf. col. 3, l. 60-66); and the insulator 20

comprises a layer of silicon dioxide (cf. col. 3, l. 56-58).

On claim 61: the insulator according to Chiang et al is made of silicon dioxide,

because said insulator is made by oxidizing part of the polysilicon layer 22 (cf. col. 3, l.

56-58); furthermore, the methods of making the $Si_{1-x}C_x$ gate as described by Halvis et al

produce $Si_{1-x}C_x$ from polycrystalline silicon thus creating crystalline silicon carbide at

least on the molecular scale, i.e., nano-crystalline silicon carbide. Finally, there is no

difference in the meaning of the verbiage "nanocrystalline" and the meaning of the

verbiage "amorphous" because even in an ultra-amorphous state nanocrystals, i.e.,

crystals at the scale of the interatomic distance, exist. Therefore, the list of crystalline

forms that constitutes the essence of this claim is not a true limitation.

8.   ***Claims 37 and 99*** are rejected under 35 U.S.C. 103(a) as being unpatentable

over Chiang et al (4,598,305) in view of Halvis et al (5,369,040). Chiang et al teach (cf.

Fig. 1) a transistor comprising a source region, a drain region, a channel region

between the source and drain regions (regions 26, 28 are the source/drain regions, and

16 is a channel region) (cf. col. 3, l. 32-66); and a (polysilicon) gate 22 separated from

the channel region by an insulator 20 (cf. col. 3, l. 32-66). The gate 22 according to

Chiang is of silicon (cf. col. 3, l. 32-66). Although Chiang et al do not necessarily teach

the gate material to be $Si_{1-x}C_x$ with x between approximately 0.5 and 1.0, it would have

been obvious to replace the poly-silicon gate material with $Si_{1-x}C_x$ with x falling in the

range between approximately 0.5 and 1.0 in view of Halvis et al, who teach in the art of

MOS photo-detectors (cf. title and abstract), hence analogous art, that the gate can be made more transparent by adding up to 50% carbon to the poly-silicon, thus creating a polycrystalline silicon carbide compound gate, thereby increasing the efficiency of the device (cf. abstract and col. 3, l. 32-43). Because the device by Chiang et al detects light that traverses the gate material there is ample motivation to include the teaching by Halvis et al in this respect in the device by Chiang et al. Combination of said teaching and said device is straightforward by adding methane gas during poly-silicon growth or using ion implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in implementing the combination can therefore be reasonably expected.

On claim 99: the insulator according to Chiang et al is made of silicon dioxide, because said insulator is made by oxidizing part of the polysilicon layer 22 (cf. col. 3, l. 56-58); furthermore, the methods of making the $Si_{1-x}C_x$ gate as described by Halvis et al produce $Si_{1-x}C_x$ from polycrystalline silicon thus creating crystalline silicon carbide at least on the molecular scale, i.e., nano-crystalline silicon carbide. Finally, there is no difference in the meaning of the verbiage "nanocrystalline" and the meaning of the verbiage "amorphous" because even in an ultra-amorphous state nanocrystals, i.e., crystals at the scale of the interatomic distance, exist. Therefore, the list of crystalline forms that constitutes the essence of this claim is not a true limitation.

9.   ***Claim 62-67*** are rejected under 35 U.S.C. 103(a) as being unpatentable over Chiang et al (4,598,305) in view of Halvis et al (5,369,040).

On claims 62-63: Chiang et al teach (cf. Fig. 1) a transistor comprising a source

region formed in a substrate and a drain region formed in the substrate (regions 26, 28

are the source/drain regions, and 12/14/26/28 is the substrate) (cf. col. 3, l. 32-66); a

channel region 16 in the substrate between the source region and the drain region (cf.

col. 3, l. 32-66); and a (polysilicon) gate 22 separated from the channel region by an

insulator 20 (cf. col. 3, l. 32-66). The gate 22 according to Chiang is of silicon (cf. col. 3,

l. 32-66). Although Chiang et al do not necessarily teach the gate material to be $Si_{1-x}C_x$

with x between 0.1 and 0.5, it would have been obvious to replace the polysilicon gate

material with $Si_{1-x}C_x$ with x between 0.1 and 0.5 in view of Halvis et al, who teach in the

art of MOS photodetectors (cf. title and abstract), hence analogous art, that the gate can

be made more transparent by adding up to 50% carbon to the polysilicon, thus creating

a polycrystalline silicon carbide compound gate (therefore, the added further limitation

defined by *claim 64* is met), thereby increasing the efficiency of the device (cf. abstract

and col. 3, l. 32-43). Because the device by Chiang et al detects light that traverses the

gate material there is ample motivation to include the teaching by Halvis et al in this

respect in the device by Chiang et al. Combination of said teaching and said device is

straightforward by adding methane gas during polysilicon growth or using ion

implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected.

On claim 63: the substrate in Chiang et al comprises a p-type silicon substrate 14

(cf. col. 3, l. 32-66); the source and drain region comprise n+ type source and drain

regions 26 and 28 (cf. col. 3, l. 32-66); and the insulator comprises a layer of silicon

dioxide (cf. col. 3, l. 32-66) as it is grown by oxidizing the silicon layer 16.

On claims 65-67: Chiang et al teach a transistor comprising a source region

formed in a substrate and a drain region formed in the substrate (regions 26, 28 are the

source/drain regions, and 12/14/26/28 is the substrate) (cf. col. 3, l. 32-66); a channel

region 16 in the substrate between the source region and the drain region (cf. col. 3, l.

32-66); and a (polysilicon) gate 22 separated from the channel region by an insulator 20

(cf. col. 3, l. 32-66). The gate 22 according to Chiang is of silicon (cf. col. 3, l. 32-66).

Although Chiang et al do not necessarily teach the gate material to be $Si_{1-x}C_x$ with x

between 0.1 and 0.5, it would have been obvious to replace the polysilicon gate material

with $Si_{1-x}C_x$ with x between 0.1 and 0.5 in view of Halvis et al, who teach in the art of

MOS photodetectors (cf. title and abstract), hence analogous art, that the gate can be

made more transparent by adding up to 50% carbon, i.e., less than x=0.5, to the

polysilicon, thus creating a polycrystalline silicon carbide compound gate (therefore, the

added further limitation defined by claim 67 is met), thereby increasing the efficiency of

the device (cf. abstract and col. 3, l. 32-43). Because the device by Chiang et al detects

light that traverses the gate material there is ample motivation to include the teaching by

Halvis et al in this respect in the device by Chiang et al. Combination of said teaching

and said device is straightforward by adding methane gas during polysilicon growth or

using ion implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected.

On claim 66: the substrate in Chiang et al comprises a p-type silicon substrate 14

(cf. col. 3, l. 32-66); the source and drain region comprise n+ type source and drain

regions 26 and 28 (cf. col. 3, l. 32-66) in the substrate; and the insulator comprises a

layer of silicon dioxide (cf. col. 3, l. 32-66) as it is grown by oxidizing the silicon layer 16.

10.   ***Claims 71-73*** are rejected under 35 U.S.C. 103(a) as being unpatentable over

Nakamura et al (ISSN #: 0018-9383) in view of Halvis et al (5,369,040). Nakamura et al

teach a floating gate transistor comprising a source region and a drain region formed in

a substrate, a channel region in the substrate between the source region and the drain

region (cf. title, abstract, and page 1693, "Introduction" (see Figure 1) and "Operation of

the SFG Pixel", see Figure 1); a floating gate (cf. abstract and "Introduction on page

1693) separated from the channel region by an insulator, said source, drain, channel,

and insulator also being inherent in the MOS transistor (cf. abstract) taught by

Nakamura et al; and a control gate BG separated from the floating gate by an inter-gate

dielectric (if the material between the gates would not be a dielectric the gates would not

be electrically independent and hence both would be either floating or controlled). The

floating gate is made of polysilicon (double-poly process used in the implementation;

see Wolf (pp. 311-312) for definition of double-poly process; see page 1694 in

Nakamura et al, "Image Sensor Architecture", first paragraph for double-poly process by

Nakamura et al).

Nakamura et al do not necessarily teach the further limitation that the

floating gate comprises a silicon carbide compound $Si_{1-x}C_x$ with x selected between 0.5

and 1.0. However, it would have been obvious to replace the floating gate material with

$Si_{1-x}C_x$ with x between 0.1 and 0.5 in view of Halvis et al, who teach in the art of MOS

photodetectors (cf. title and abstract), hence analogous art, that the gate can be made

more transparent by adding up to 50% carbon, i.e., only infinitesimally less than x>0.5,

to the silicon, thus creating a polycrystalline silicon carbide compound gate (therefore,

the added further limitation defined by _claim 73_ is met), thereby increasing the efficiency

of the device (cf. abstract and col. 3, l. 32-43). The prior art range thus only

infinitesimally fails to overlap with the range as claimed. Applicant's disclosure does not

explain why it is critical to the invention to make x infinitesimally greater than 0.5 thus

fulfilling the limitation in the claim, instead of infinitesimally less than 0.5 as taught by

Halvis et al: the "Summary of the Invention" rather allows for the range 0 < x < 1 (see

pages 3-5), while other claims in the same invention cover rather complementary

ranges, such as 0.1 < x < 0.5. Furthermore, according to Applicant the value of x in one

embodiment is selected to establish a desired value for the barrier energy between the

gate and the underlying insulator; however, the energy gap of $Si_{1-x}C_x$, and hence said

barrier energy is a continuous function of the stoichiometric parameter x (a polynomial).

Therefore, said barrier energy has substantially the same value for x infinitesimally less

than 0.5 and for x infinitesimally greater than 0.5. The burden is to Applicant to show

otherwise, i.e., to show said infinitesimal difference in x makes a critical difference in the

invention. Applicant is reminded that a _prima facie_ case of obviousness typically exists

when the ranges of a claimed composition overlap the ranges disclosed in the prior art

or when the ranges of a claimed composition do not overlap but are close enough such

that one skilled in the art would have expected them to have the same properties. In re

Peterson, 65 USPQ2d 1379 (CA FC 2003). Because the device by Chiang et al detects

light that traverses the gate material there is ample motivation to include the teaching by

Halvis et al in this respect in the device by Chiang et al. Combination of said teaching

and said device is straightforward by adding methane gas during poly-silicon growth or

using ion implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected.

Because the device by Nakamura et al detects light that traverses the floating

gate (FG) material (because the active region is located between the n+ source and

drain regions) (see Figure 1) there is ample motivation to include the teaching by Halvis

et al in this respect in the device by Nakamura et al. Combination of said teaching and

said device is straightforward by adding methane gas during polysilicon growth or using

ion implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected.

On claim 72: Nakamura et al teach a floating gate transistor comprising a source

region and a drain region formed in a substrate, a channel region in the substrate

between the source region and the drain region (cf. title, abstract, and page 1693,

"Introduction" (see Figure 1) and "Operation of the SFG Pixel", see Figure 1); a floating

gate (cf. abstract and "Introduction on page 1693) separated from the channel region by

an insulator, said source, drain, channel, and insulator also being inherent in the MOS

transistor (cf. abstract) taught by Nakamura et al; and a control gate BG separated from

the floating gate by an inter-gate dielectric (if the material between the gates would not

be a dielectric the gates would not be electrically independent and hence both would be

either floating or controlled). The floating gate is made of polysilicon (double-poly

process used in the implementation; see Wolf (pp. 311-312) for definition of double-poly

process; see page 1694 in Nakamura et al, "Image Sensor Architecture", first paragraph

for double-poly process by Nakamura et al).

11.   ***Claims 74 and 76*** are rejected under 35 U.S.C. 103(a) as being unpatentable

over Nakamura et al (ISSN #: 0018-9383) in view of Halvis et al (5,369,040). Nakamura

et al teach a floating gate transistor comprising a source region and a drain region

formed in a substrate, a channel region in the substrate between the source region and

the drain region (cf. title, abstract, and page 1693, "Introduction" (see Figure 1) and

"Operation of the SFG Pixel", see Figure 1); a floating gate (cf. abstract and

"Introduction on page 1693) separated from the channel region by an insulator, said

source, drain, channel, and insulator also being inherent in the MOS transistor (cf.

abstract) taught by Nakamura et al; and a control gate BG separated from the floating

gate by an inter-gate dielectric (if the material between the gates would not be a

dielectric the gates would not be electrically independent and hence both would be

either floating or controlled). The floating gate is made of polysilicon (double-poly

process used in the implementation; see Wolf (pp. 311-312) for definition of double-poly

process; see page 1694 in Nakamura et al, "Image Sensor Architecture", first paragraph

for double-poly process by Nakamura et al).

Nakamura et al do not necessarily teach the further limitation that the floating gate comprises a silicon carbide compound $Si_{1-x}C_x$ with x selected between 0.1 and 0.5. However, it would have been obvious to replace the floating gate material with $Si_{1-x}C_x$ with x between 0.1 and 0.5 in view of Halvis et al, who teach in the art of MOS photodetectors (cf. title and abstract), hence analogous art, that the gate can be made more transparent by adding up to 50% carbon, i.e., less than x=0.5, to the silicon, thus creating a polycrystalline silicon carbide compound gate (therefore, the added further limitation defined by *claim 76* is met), thereby increasing the efficiency of the device (cf. abstract and col. 3, l. 32-43). The range x<0.5 completely includes the range by Applicant while the preferred value of x being approximately 10% still is in the range of Applicant. Because the device by Nakamura et al detects light that traverses the floating gate (FG) material (because the active region is located between the n+ source and drain regions) (see Figure 1) there is ample motivation to include the teaching by Halvis et al in this respect in the device by Nakamura et al. Combination of said teaching and said device is straightforward by adding methane gas during polysilicon growth or using ion implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in implementing the combination can therefore be reasonably expected.

12.   *Claim 75* is rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura et al and Halvis et al as applied to claim 74 above, and further in view of Chiang et al (4,598). As detailed above, independent claim 74 is unpatentable over Nakamura et al in view of Halvis et al. Furthermore, the substrate in the device by

Nakamura et al comprises a p-type silicon substrate p (cf. Figure 1 and page 1694,

"Image Sensor Architecture", first paragraph, referring to double-poly CMOS process;

see Wolf pages 311-312 for definition of double-poly CMOS process); the source and

drain region comprise n+ type source and drain regions n+ (cf. col. 3, l. 32-66); and the

insulator comprises a layer of silicon dioxide (cf. col. 3, l. 32-66) as it is grown by

oxidizing the silicon layer 16. Although neither Nakamura et al nor Halvis et al

necessarily teach the insulator to be of silicon dioxide, silicon dioxide is a preferred

selection for the gate insulation layer in any MOSFET because of its ease of making

and has been used by for instance Chiang et al in the analogous art of MOS

photodetectors (cf. Figure 1, col. 3, l. 56-58), in which one of the requirements involves

the relative transparency of the gate insulator material to light.

Motivation to include the teaching by Chiang et al in the device as essentially

taught by Nakamura et al and Halvis et al stems from said relative ease of making

according to the method delineated by Chiang et al (cf. col. 3, l. 56-58) and from said

relative transparency to light. Combination of said teaching with said device merely

involves a standard step in the double-poly process followed by Nakamura et al through

which the entire device can be made starting from silicon.

13.   *Claims 77 and 79* are rejected under 35 U.S.C. 103(a) as being unpatentable

over Nakamura et al (ISSN #: 0018-9383) in view of Halvis et al (5,369,040). Nakamura

et al teach a floating gate transistor comprising a source region and a drain region

formed in a substrate, a channel region in the substrate between the source region and

the drain region (cf. title, abstract, and page 1693, "Introduction" (see Figure 1) and

"Operation of the SFG Pixel", see Figure 1); a floating gate (cf. abstract and

"Introduction on page 1693) separated from the channel region by an insulator, said

source, drain, channel, and insulator also being inherent in the MOS transistor (cf.

abstract) taught by Nakamura et al; and a control gate BG separated from the floating

gate by an inter-gate dielectric (if the material between the gates would not be a

dielectric the gates would not be electrically independent and hence both would be

either floating or controlled). The floating gate is made of polysilicon (double-poly

process used in the implementation; see Wolf (pp. 311-312) for definition of double-poly

process; see page 1694 in Nakamura et al, "Image Sensor Architecture", first paragraph

for double-poly process by Nakamura et al).

    Nakamura et al do not necessarily teach the further limitation that the

floating gate comprises a silicon carbide compound $Si_{1-x}C_x$ with x selected to be less

than 0.5. However, it would have been obvious to replace the floating gate material with

$Si_{1-x}C_x$ with x less than 0.5 in view of Halvis et al, who teach in the art of MOS

photodetectors (cf. title and abstract), hence analogous art, that the gate can be made

more transparent by adding up to 50% carbon, i.e., less than x=0.5, to the silicon, thus

creating a polycrystalline silicon carbide compound gate (therefore, the added further

limitation defined by *claim 79* is met), thereby increasing the efficiency of the device (cf.

abstract and col. 3, l. 32-43). Because the device by Nakamura et al detects light that

traverses the floating gate (FG) material (because the active region is located between

the n+ source and drain regions) (see Figure 1) there is ample motivation to include the

teaching by Halvis et al in this respect in the device by Nakamura et al. Combination of

said teaching and said device is straightforward by adding methane gas during

polysilicon growth or using ion implantation as recommended by Halvis et al (cf. col. 3, l.

44-51). Success in implementing the combination can therefore be reasonably

expected.

14.   *Claim 75* is rejected under 35 U.S.C. 103(a) as being unpatentable over

Nakamura et al and Halvis et al as applied to claim 74 above, and further in view of

Chiang et al (4,598). As detailed above, independent claim 74 is unpatentable over

Nakamura et al in view of Halvis et al. Furthermore, the substrate in the device by

Nakamura et al comprises a p-type silicon substrate p (cf. Figure 1 and page 1694,

"Image Sensor Architecture", first paragraph, referring to double-poly CMOS process;

see Wolf pages 311-312 for definition of double-poly CMOS process); the source and

drain region comprise n+ type source and drain regions n+ (cf. col. 3, l. 32-66); and the

insulator comprises a layer of silicon dioxide (cf. col. 3, l. 32-66) as it is grown by

oxidizing the silicon layer 16. Although neither Nakamura et al nor Halvis et al

necessarily teach the insulator to be of silicon dioxide, silicon dioxide is a preferred

selection for the gate insulation layer in any MOSFET because of its ease of making

and has been used by for instance Chiang et al in the analogous art of MOS

photodetectors (cf. Figure 1, col. 3, l. 56-58), in which one of the requirements involves

the relative transparency of the gate insulator material to light.

Motivation to include the teaching by Chiang et al in the device as essentially

taught by Nakamura et al and Halvis et al stems from said relative ease of making

according to the method delineated by Chiang et al (cf. col. 3, l. 56-58) and from said

relative transparency to light. Combination of said teaching with said device merely

involves a standard step in the double-poly process followed by Nakamura et al through

which the entire device can be made starting from silicon.

15.   *Claim 78* is rejected under 35 U.S.C. 103(a) as being unpatentable over

Nakamura et al and Halvis et al as applied to claim 77 above, and further in view of

Chiang et al (4,598). As detailed above, independent claim 77 is unpatentable over

Nakamura et al in view of Halvis et al. Furthermore, the substrate in the device by

Nakamura et al comprises a p-type silicon substrate p (cf. Figure 1 and page 1694,

"Image Sensor Architecture", first paragraph, referring to double-poly CMOS process;

see Wolf pages 311-312 for definition of double-poly CMOS process); the source and

drain region comprise n+ type source and drain regions n+ (cf. col. 3, l. 32-66); and the

insulator comprises a layer of silicon dioxide (cf. col. 3, l. 32-66) as it is grown by

oxidizing the silicon layer 16. Although neither Nakamura et al nor Halvis et al

necessarily teach the insulator to be of silicon dioxide, silicon dioxide is a preferred

selection for the gate insulation layer in any MOSFET because of its ease of making

and has been used by for instance Chiang et al in the analogous art of MOS

photodetectors (cf. Figure 1, col. 3, l. 56-58), in which one of the requirements involves

the relative transparency of the gate insulator material to light.

Motivation to include the teaching by Chiang et al in the device as essentially

taught by Nakamura et al and Halvis et al stems from said relative ease of making

according to the method delineated by Chiang et al (cf. col. 3, l. 56-58) and from said

relative transparency to light. Combination of said teaching with said device merely

involves a standard step in the double-poly process followed by Nakamura et al through

which the entire device can be made starting from silicon.

16.   *Claims 80-82* are rejected under 35 U.S.C. 103(a) as being unpatentable over

Nakamura et al ((ISSN #: 0018-9383) in view of Halvis et al (5,369,040). Nakamura et al

teach a floating gate transistor comprising a source region and a drain region formed in

a substrate, a channel region in the substrate between the source region and the drain

region (cf. title, abstract, and page 1693, "Introduction" (see Figure 1) and "Operation of

the SFG Pixel", see Figure 1); a floating gate (cf. abstract and "Introduction on page

1693) separated from the channel region by an insulator, said source, drain, channel,

and insulator also being inherent in the MOS transistor (cf. abstract) taught by

Nakamura et al; and a control gate BG separated from the floating gate by an inter-gate

dielectric (if the material between the gates would not be a dielectric the gates would not

be electrically independent and hence both would be either floating or controlled). The

floating gate is made of polysilicon (double-poly process used in the implementation;

see Wolf (pp. 311-312) for definition of double-poly process; see page 1694 in

Nakamura et al, "Image Sensor Architecture", first paragraph for double-poly process by

Nakamura et al).

Nakamura et al do not necessarily teach the further limitation that the floating gate comprises a silicon carbide compound $Si_{1-x}C_x$ with x selected to be between 0.5 and 0.75. However, it would have been obvious to replace the floating gate material with $Si_{1-x}C_x$ with x only infinitesimally less than 0.5 in view of Halvis et al, who teach in the art of MOS photodetectors (cf. title and abstract), hence analogous art, that the gate can be made more transparent by adding up to 50% carbon, i.e., up to infinitesimally less than x=0.5, to the silicon, thus creating a polycrystalline silicon carbide compound gate (therefore, the added further limitation defined by *claim 82* is met), thereby increasing the efficiency of the device (cf. abstract and col. 3, l. 32-43).

The prior art range thus only infinitesimally fails to overlap with the range as claimed. Applicant's disclosure does not explain why it is critical to the invention to make x infinitesimally greater than 0.5 thus fulfilling the limitation in the claim, instead of infinitesimally less than 0.5 as taught by Halvis et al: the "Summary of the Invention" rather allows for the range $0 < x < 1$ (see pages 3-5), while other claims in the same invention cover rather complementary ranges, such as $0.1 < x < 0.5$. Furthermore, according to Applicant the value of x in one embodiment is selected to establish a desired value for the barrier energy between the gate and the underlying insulator; however, the energy gap of $Si_{1-x}C_x$, and hence said barrier energy is a continuous function of the stoichiometric parameter x (a polynomial). Therefore, said barrier energy has substantially the same value for x infinitesimally less than 0.5 and for x infinitesimally greater than 0.5. The burden is to Applicant to show otherwise, i.e., to show said infinitesimal difference in x makes a critical difference in the invention.

Applicant is reminded that a *prima facie* case of obviousness typically exists when the

ranges of a claimed composition overlap the ranges disclosed in the prior art or when

the ranges of a claimed composition do not overlap but are close enough such that one

skilled in the art would have expected them to have the same properties. In re Peterson,

65 USPQ2d 1379 (CA FC 2003). Because the device by Chiang et al detects light that

traverses the gate material there is ample motivation to include the teaching by Halvis et

al in this respect in the device by Chiang et al. Combination of said teaching and said

device is straightforward by adding methane gas during poly-silicon growth or using ion

implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected.

Because the device by Nakamura et al detects light that traverses the floating

gate (FG) material (because the active region is located between the n+ source and

drain regions) (see Figure 1) there is ample motivation to include the teaching by Halvis

et al in this respect in the device by Nakamura et al. Combination of said teaching and

said device is straightforward by adding methane gas during polysilicon growth or using

ion implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected.

On claim 81: Nakamura et al teach a floating gate transistor comprising a source

region and a drain region formed in a substrate, a channel region in the substrate

between the source region and the drain region (cf. title, abstract, and page 1693,

"Introduction" (see Figure 1) and "Operation of the SFG Pixel", see Figure 1); a floating

gate (cf. abstract and "Introduction on page 1693) separated from the channel region by

an insulator, said source, drain, channel, and insulator also being inherent in the MOS

transistor (cf. abstract) taught by Nakamura et al; and a control gate BG separated from

the floating gate by an inter-gate dielectric (if the material between the gates would not

be a dielectric the gates would not be electrically independent and hence both would be

either floating or controlled). The floating gate is made of polysilicon (double-poly

process used in the implementation; see Wolf (pp. 311-312) for definition of double-poly

process; see page 1694 in Nakamura et al, "Image Sensor Architecture", first paragraph

for double-poly process by Nakamura et al).

17.   *Claims 36 and 98* are rejected under 35 U.S.C. 103(a) as being unpatentable

over Nakamura et al (ISSN #: 0018-9383) in view of Halvis et al (5,369,040). Nakamura

et al teach a floating gate transistor comprising a source region and a drain region (n+

regions in the p substrate; cf. Figure 1), a channel region in the substrate between the

source region and the drain region (cf. title, abstract, and page 1693, "Introduction" (see

Figure 1) and "Operation of the SFG Pixel", see Figure 1); and a (floating) gate (cf.

abstract and "Introduction on page 1693) separated from the channel region by an

insulator. Said source, drain, channel, and insulator also being inherent in the MOS

transistor (cf. abstract) taught by Nakamura et al; and a control gate BG separated from

the floating gate by an inter-gate dielectric (if the material between the gates would not

be a dielectric the gates would not be electrically independent and hence both would be

either floating or controlled). The (floating) gate is made of polysilicon (double-poly

process used in the implementation; see Wolf (pp. 311-312) for definition of double-poly

process; see page 1694 in Nakamura et al, "Image Sensor Architecture", first paragraph

for double-poly process by Nakamura et al).

   Nakamura et al do not necessarily teach the further limitation that the

floating gate comprises a silicon carbide compound $Si_{1-x}C_x$ with x selected to be greater

than 0.5. However, it would have been obvious to replace the floating gate material with

$Si_{1-x}C_x$ with x between 0.1 and 0.5 in view of Halvis et al, who teach in the art of MOS

photodetectors (cf. title and abstract), hence analogous art, that the floating gate can be

made more transparent by adding up to 50% carbon, i.e., only infinitesimally less than

x>0.5, to the silicon, thereby increasing the efficiency of the device (cf. abstract and col.

3, l. 32-43). The prior art range thus only infinitesimally fails to overlap with the range as

claimed. Applicant's disclosure does not explain why it is critical to the invention to

make x infinitesimally greater than 0.5 thus fulfilling the limitation in the claim, instead of

infinitesimally less than 0.5 as taught by Halvis et al: the "Summary of the Invention"

rather allows for the range 0 < x < 1 (see pages 3-5), while other claims in the same

invention cover rather complementary ranges, such as 0.1 < x < 0.5. Furthermore,

according to Applicant the value of x in one embodiment is selected to establish a

desired value for the barrier energy between the gate and the underlying insulator;

however, the energy gap of $Si_{1-x}C_x$, and hence said barrier energy is a continuous

function of the stoichiometric parameter x (a polynomial). Therefore, said barrier energy

has substantially the same value for x infinitesimally less than 0.5 and for x

infinitesimally greater than 0.5. The burden is to Applicant to show otherwise, i.e., to

show said infinitesimal difference in x makes a critical difference in the invention.

Applicant is reminded that a *prima facie* case of obviousness typically exists when the

ranges of a claimed composition overlap the ranges disclosed in the prior art or when

the ranges of a claimed composition do not overlap but are close enough such that one

skilled in the art would have expected them to have the same properties. In re Peterson,

65 USPQ2d 1379 (CA FC 2003). Because the device by Chiang et al detects light that

traverses the gate material there is ample motivation to include the teaching by Halvis et

al in this respect in the device by Chiang et al. Combination of said teaching and said

device is straightforward by adding methane gas during poly-silicon growth or using ion

implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected. Because the

device by Nakamura et al detects light that traverses the floating gate (FG) material

(because the active region is located between the n+ source and drain regions) (see

Figure 1) there is ample motivation to include the teaching by Halvis et al in this respect

in the device by Nakamura et al. Combination of said teaching and said device is

straightforward by adding methane gas during polysilicon growth or using ion

implantation as recommended by Halvis et al (cf. col. 3, l. 44-51). Success in

implementing the combination can therefore be reasonably expected.

On claim 98: as mentioned, said gate is a floating gate (FG) (cf. Figure 1 and loc.

cit.), and the device by Nakamura et al further comprises a control gate BG separated

from said floating gate by an inter-gate dielectric comprising silicon dioxide.

Allowable Subject Matter

18.   ***Claims 83-85*** are allowable over the prior art. The following is a statement of

reasons for the indication of allowable subject matter: a floating gate transistor with

source, drain, channel and gate insulator with floating gate and control gate is in the

prior art (Nakamura et al, loc.cit.). However, the limitation that the floating gate material

comprises a silicon carbide compound $Si_{1-x}C_x$ wherein x is selected between 0.75 and

1.0 has not been found (the closest value for the stoichiometric parameter x found in the

prior art was a limit point of 0.5). Previously cited rejection over Fujiwara (5,798,548) in

view of Weitzel et al (5,661,312) and Hamakawa et al (JP357126175A) has been

withdrawn: although the examiner maintains that material selection by Weitzel et al for

the gate has been prompted by breakdown considerations as delineated in the previous

Office Action (Paper No. 16, "Response to Arguments") (see especially col. 1, l. 58-60)

the art by Hamakawa et al is insufficiently analogous to conclude obviousness: the lack

of analogy stems mainly from the PIN diode rather than field effect type device taught

by Hamakawa et al (see English abstract). Although carbon (Si_0C_1) gates in insulated

gate field effect transistors are known (e.g., Ukai et al, 5,910,665), their inclusion

together with a control gate, the carbon gate being a floating gate, has not been found

to date.

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Johannes P Mondt whose telephone number is 703-

306-0531. The examiner can normally be reached on 8:00 - 18:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Nathan J Flynn can be reached on 703-308-6601. The fax phone number

for the organization where this application or proceeding is assigned is (703) 872-9306.

Any inquiry of a general nature or relating to the status of this application or

proceeding should be directed to the receptionist whose telephone number is 703-308-

0956.

JPM
August 19, 2003

NATHAN J. FLYNN
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2800